

Options and Accessories

Site Lighting and Building-Mounted Lighting


■ = Available as an option, shipped installed
 □ = Available as an accessory, shipped separately

		KBA	KBC	KBD	KBE	KBR	KBS	KL	VV	TWH	TWP	TWA	TWL	WG/WP	WFL
BBF	Backbox for flat surfaces.							■							
BBP	Backbox with pole.							□							
BBR	Backbox, recessed (ceiling, soffit mount).							■							
BBS	Backbox for stud wall construction.							■							
BBW	Backbox for surface wall installation.							■							□
EP1	Extension collar, 1-1/2" deep. Requires caulk for wet locations. Order as TWLEP1.														□
EP2	Extension collar, 2-1/8" deep. Requires caulk for wet locations. Order as TWLEP2.														□
FS	Full Shield for cut-off distribution									■	■				
HS	House-side shield								■						
PC	Polycarbonate lens. Standard on KL.	■	■	■	■	■	■	■	■						
R6S/R8S	Half-Shield. Not for use with louvered bollards.	□	□	□			□								
S6S/S8S	Half-Shield. Not for use with louvered bollards.				□		□								
SCL	Scribed Lens. Not available with louvered bollards.	■	■	■	■	■	■								
TS2	2-3/8" (6.0) tenon.								■						
TS3	3" (7.6) tenon.								■						
TS35	3-1/2" (8.9) tenon.								■						
TS4	4" (10.1) tenon.								■						
TWAWG	Wireguard.											□	□ ³		
TWHVG²	Vandal Guard. Ships as TWHVG U ¹ and TWHVG J4 ¹ .									□					
TWHWG²	Wireguard. Ships as TWHWG U ¹ .									■					
TWLMB	Mounting Box, cast aluminum.												□		
TWLWG	Wireguard. Ships as TWLWG U ¹ .												□ ⁴		
TWPWG	Wireguard. Use with TWP. Ships as TWPWG U ¹ .										□				


NOTES:

- 1 Constructed of hot-dipped galvanized steel wire.
- 2 Housing modification required.
- 3 For use with TWL, HPF unit with backbox.
- 4 For TWL HPF unit only. For TWL HPF unit use TWAWG.


TWHVG




TWPWG




TWHWG




BBF




BBP




BBS




BBW




TWAWG




TWLWG



EP1



TWLMB



Garage Lighting and Sportlighting

■ = Available as an option, shipped installed
 □ = Available as an accessory, shipped separately

		PGR	KPS	KACM	TSP	TV	THT
RMG	Recessed Mount in grid ceiling	■					
SS	Stainless Steel Ceiling Mount. Housing constructed of alloy 304 stainless steel with 28 longitudinal finish. Finish options include NB - Natural Brushed or CR -Corrosion-Resistant clear polyester powder.	■					
AH	Above horizontal aiming					■	
CF	Charcoal Filter. Must use with heavy duty or heavy duty shroud.				■	■	
CH	Die Cast Housing.					■	
CRA	Cross-Arm Adaptor for horizontal mounting. Order as separate catalog number. Ships as CRA U & CRAJ4.				□	□	
CRA45	Cross-Arm Adaptor for horizontal mounting 45°. Order as separate catalog number. Ships as CRA45 U, CRA45 J4 and CRA45 J12. Standard on TSP.					□	
SLR	Stainless Steel Lens Rings.				■	■	
IBL	Internal Bottom Louver. Can not order IBL and TVUV together.					■	
TVPMB	Pole Mounting Bracket. Use on round pole. Ships as TVPMB U.				□	□	
TVPWB	Wood Pole or Wall Mounting Bracket.				□	□	
TVRAB	Right Angle Mounting Bracket. Ships as TVRAB U. Standard finish is DDB.			□	□		
TVSAB	Steel Angle Mounting Bracket. Standard finish is dark bronze (must specify color). Ships as TVSAB U.				□	□	
TVTS	Tenon Slipfitter. Fits 2" to 2-1/2" pipe. Ships as TVTS U, J4 and J12.				□	□	
TVUV	Upper Visor.					□	
TVX2	2-Light Wood Pole Cross-Arm. Order as separate catalog number.				□	□	
TVX3	3-Light Wood Pole Cross-Arm. Order as separate catalog number.				□	□	
TVX4	4-Light Wood Pole Cross-Arm. Order as separate catalog number.				□	□	
TVWC	Wood Cross-Arm Mounting Bolt 5/8" - 11 UNC. 8" length. Ships as TVWC U and TVWC J4.				□	□	
YK	Yoke Mount.	□	□				

